



Mosaic™ Cable outlets and branching device


Cat. No(s): 0 775 50/51/52/53 - 0 791 50L - 0 792 49



0 775 52



0 775 51



0 775 53


1. USE

Cable outlets and wires for cables of different diameters.
 Mechanisms are flush-mounted or surface-mounted.

2. RANGE

	White	Alu	Matt Black
Branching device with 3 terminals 2 modules	0 775 53	-	-
Equipped cable outlet with cable clamps max. Ø to be used 12 mm, min. Ø to be used 4 mm 2 modules	0 775 51	-	-
Cable outlet with cable clamps max. Ø to be used 12 mm, min. Ø to be used 4 mm Authorized cables H05 VVF or H07 RNF 2 modules	0 775 50	0 792 49	0 791 50L
Wire outlet Ø 8 mm 1 module	0 775 52	-	-

3. DIMENSIONS (mm)



Cat. Nos	A	B	C	D
0 775 50 - 0 791 50L - 0 792 49	45	45	39	20
0 775 51	45	45	49.5	20
0 775 52	45	22.5	24.5	-
0 775 53	45	45	32.5	12.5

4. CONNECTION

Cat. No 0 775 51

Type of terminals: automatic
 Stripping length: 12 mm
 Cable cross-section: 4 x 2 x 1.5 mm²

Cat. No 0 775 53

Type of terminals: with screws
 Stripping length: 12 mm
 Cable cross-section: 6 x 2.5 mm²
 Screwdriver: Philips n° 1

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 41
 Protection against impact: IK 04

■ 5.2 Material characteristics

Base: PC
 Cover plate:
 Cat. No 0 775 52/53: PC White (RAL 9003)
 Cat. No 0 775 50: ABS White RAL 9003
 Cat. No 0 791 50L: ABS painted Matt Black satin finish RAL 9017
 Cat. No 0 792 49: ABS painted Aluminium varnished glittery
 Halogen free
 UV resistant
 Self-extinguishing: 650° C / 30 s

■ 5.3 Electrical characteristics

Voltage: 250 V~
 Current: 10 A for Cat No 0 775 51
 20 A for Cat No 0 775 53

■ 5.4 Climatic characteristics

Storage temperature: - 10° C to + 70° C
 Use temperature: - 5° C to + 35° C

6. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.
 Resistance to the cleaning agents: Hexane (NF C 61-314), Methylated spirit, Soapy water, Diluted ammonia, Diluted pure bleach 10%, Glass cleaning substances, Pre-impregnated wipes.
 Anios, Surfianos, Bactilycine, Diluted hydrogen peroxide (35 %).

Caution: A preliminary test should be carried out if other specific cleaning products are to be used.

7. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing.
See e.catalogue.