



Termoplástico
Termoplastico
Thermoplastic
Thermoplastique



-5°C
+60°C



Autoextinguível
Autoextinguible
Self extinguishing
Autoextinguible



Teste Fio Incandescente
Prueba Hilo Incandescente
Glow Wire Test
Test of Fil Incandescent

Ref. + M0 960°

Ref. + M2 850°



Fecho com parafuso a 3/4
Cierre por tornillos a 3/4
Closed by screws a 3/4
Ferme par des vis a 3/4



Branco | Cinza | Creme | Preto
Blanco | Gris | Crema | Negro
White | Gray | Cream | Black
Blanc | Gris | Crème | Noir



Chave
Llave
Key
Clé



SERIE 200 CLASSIC



Caixas estanques com paredes lisas
Cajas estancas con paredes lisas
Cable junction enclosures with plain walls
Boîtes de dérivation étanches non percées



Ref.		Dim. Ext.(mm)	IP	IK
220L	750°	81x81x43	55	08
222L	750°	100x100x54	65	09
221L	750°	148x108x72	65	09
223L	750°	174x108x61	65	09
223LTA	750°	174x108x83	65	09
225L	750°	187x148x70	65	09
225LTA	750°	187x148x92	65	09
226L	750°	217x168x120	65	09
224L	750°	217x168x100	65	09
MF-242	750°	323x275x178	65	09
MF-244	750°	420x380x178	54	09



SCAN + INFO

Todas as referências poderão ser fabricadas em:
Todas las referencias pueden ser fabricadas en:
All references may be produced in:
Toutes les références peuvent être faites à:

M2 850°C

M0 960°C

Ex.: J80-L ref. + M2 850°C = J80-L M2 ref.