

# LUMINARIAS LED Y SISTEMAS DE ILUMINACIÓN LED LIGHTING SYSTEM



## PANTALLA NBA 12V-24V DC & 24V ACDC

### 12-24CC o 24CCCA.

Disponibles en dos versiones, con driver válido entre 12 y 24V en continua o con driver específico 24V ACDC. Este último permite una entrada de tensión tanto en alterna como en continua, muy útil para instalaciones con transformador de seguridad en fosos, casetas de piscina o zonas húmedas así como en vehículos o embarcaciones donde se pasa de batería a alternador.

### 12-24DC OR 24ACDC.

Available in two versions, with driver valid between 12 and 24V DC or with specific driver 24V ACDC. The last one allows a voltage input in both AC and DC, very useful for installations with safety transformer in pits, pool huts or wet areas as well as in vehicles or vessels where battery is passed to alternator.

## PANTALLA NBA 12V-24V DC & 24V ACDC



Pantalla  
NBA

Modelo Model	LPL06N24ACDC	LPL12N24ACDC	LPL06N1224	LPL12N1224
Rango de tensión Voltage range	24V ACDC	24V ACDC	12V-24V DC	12V-24V DC
Potencia Power	20W	40W	20W	40W
Flujo lumínico Lumen	2217Lm	4434Lm	2217Lm	4434Lm
Temperatura de color Color temperature	5000K□	5000K□	5000K□	5000K□
Ángulo Angle	120°	120°	120°	120°
Largo Length	600mm	1200mm	600mm	1200mm
Ancho x Alto Width x Height	80x65mm	80x65mm	80x65mm	80x65mm
Base y difusor Base and diffuser	PC	PC	PC	PC
IP	65	65	65	65
IK	IK10	IK10	IK10	IK10



24V ACDC  
12V-24V DC



LPL06N24ACDC  
LPL12N24ACDC  
LPL06N1224  
LPL12N1224



Vídeos demostrativos:  
[www.pritec.com/videos](http://www.pritec.com/videos)



118