

Product Datasheet Date: 27.02.2020

# **General Data**

Article No.	ZLFA0945
Code	RAL1/HOLDER/S14D
Product EAN	4003556001237
Customs tariff no.	85366190
Box quantitiy (pcs.)	100
EAN Box	4003556401235
ETIM class	EC000401
ETIM class name	Lamp holder
Product status	Active

### **Electric Parameters**

Nominal voltage 230	30 V
---------------------	------





# RaleDina lamp holders, RAL1/HOLDER/S14D



## **Specification**

Length	82 mm
Height h max.	46 mm
Width b max.	34 mm
Model	Plug-in lamp holder
Base	S14d
Colour	Grey

### **Notes on Operation**

Lam	q	RAL1

#### **Notes**

Lamp holder S14d for double-based linear lamps, to be installed by qualified personnel only (electrician).

Please, refer to <a href="www.radium.de/recycling">www.radium.de/recycling</a> for notes on disposal of burned-out lamps as well as lamp breakage. The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

## RaLEDina lamp holders, RAL1/HOLDER/S14D



#### **Notes**

#### **Base**



S14d IEC/EN 60061-1 sheet 7004-112-1

#### General notes

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

### Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.