


General Data

Article No.	HIBA1769
Code	LED HIGHBAY 120W/6500K BK IP44
Product EAN	4003556005853
Customs tariff no.	94051040
Box quantity (pcs.)	1
EAN Box	4003556005853
Gross weight of box in kg	2464
Length of box in m	0.39
Width of box in m	0.39
Height of box in m	0.28
ETIM class	EC001716
ETIM class name	High bay luminaire
Weight	2000 g
Product status	Inactive

**Electric Parameters**

Nominal power	120 W
Energy Consumption kWh/1000h	120
Power factor	≥ 0.9
Nominal voltage	220-240 V
Voltage type	AC
Inrush current	33 A
Supply frequency	50 ... 60 Hz
Suitable for lamp power	≥ 80 W
dimnable	No

Light Application Parameters

Beam angle	90 °
Glare value	UGR ≤ 30
Luminous efficiency	100 lm/W
Colour of light	White
Colour temperature	6500 K
Colour rendering index CRI	80-89
Colour Stability	≤ 5 sdc
Light sharing	Symmetric

Service Life

Lifetime L70B50	30000 h
-----------------	---------

Specification

Diameter	350 mm
Height	220 mm
Built-in width	nicht dimmbar mm
Cable Length	0,5 m
Impact strength	IK07

Notes on Operation

Degree of protection (IP)	IP44
Mode of operation	with external LED driver
Type of connection	Feed-in cable, 3-pole
Max. number of luminaires per B10 circuit breaker	14
Max. number of luminaires per B16 circuit breaker	23
Max. number of luminaires per C16 circuit breaker	23
Suitable for lamp power	≥80 W
Permissible storage temperature	-40...+70 °C
Ambient temperatures	-20...40 °C
Luminaire with limited surface temperature, sign "D"	No
Mounting method	Pendant
Type of control gear	LED operating device current-controlled

Notes

Light source for high halls and large areas, integrated LED driver, little glare due to reflector design and deep-seated LED module, non-dim.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage. The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Notes**Special features****General notes**

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.