LED luminaire for humid environment, LED DAMPPROOF 1500 48W/6500K IP65



Product Datasheet Date: 13.02.2020


General Data

Article No.	DAPA1782
Code	LED DAMPPROOF 1500 48W/6500K IP65
Product EAN	4003556005891
Customs tariff no.	94051040
Box quantitiy (pcs.)	8
EAN Box	4003556405899
Gross weight of box in kg	15553
Length of box in m	1.53
Width of box in m	0.2
Height of box in m	0.33
ETIM class	EC002892
ETIM class name	Ceiling-/wall luminaire
Product status	Phase Out



Electric Parameters

Nominal voltage	220-240 V
Voltage type	AC



Light Application Parameters

Colour of light	White
Colour rendering index CRI	80-89

LED luminaire for humid environment, LED DAMPPROOF 1500 48W/6500K IP65



Specification

Material	PC
Notes on Operation	
Degree of protection (IP)	IP65
Mounting type	Surface mounting

Notes

Robust, classic design for humid or dusty environment. Simple mounting, very homogeneous light with wide beam angle, non-dim.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage. The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

LED luminaire for humid environment, LED DAMPPROOF 1500 48W/6500K IP65



Notes

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

§ = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.