


# NEW Silent Fan

- From only 12dB(A)
- IPX5 - Zone 1 rated
- Meets current Building Regulations Approved Document F and L
- Extra-long duct run? Models available with speeds adjustable at installation to get the airflow you need
- 8 model variants
- Silent bathroom fan with intermittent and continuous running options
- Back draught shutters included
- High efficiency motor
- Up to 5 year warranty
- Suitable for wall, ceiling, window and panel mounting



## Silent Fan Axial Bathroom/Toilet Fan

The new Silent Fan Range from Vent-Axia not only delivers stylish and silent ventilation without compromise on performance, but now comes with even more features and more model options providing flexibility when choosing the right fan.



### Models

#### VASF100B (Fixed Speed, Intermittent)

Remote or light switch operation. 2 speed options selectable at install. Intermittent operation.

**Model** VASF100B **Stock Ref** 446658

#### VASF100T (Fixed Speed, Intermittent, Timer)

Overrun timer adjustable 5-30 min. 2 speed options selectable at install. Intermittent operation.

**Model** VASF100T **Stock Ref** 446659

#### VASF100HT (Fixed Speed, Intermittent, Humidity Timer)

Humidity controlled with fixed 15 min timer overrun. 2 speed options selectable at install. Intermittent operation.

**Model** VASF100HT **Stock Ref** 477436

#### VASF100BV (Variable Speed, Intermittent)

Remote or light switch operation. Variable speed options selectable at install. Intermittent operation.

**Model** VASF100BV **Stock Ref** 479085

#### VASF100TV (Variable Speed, Intermittent, Timer)

Intermittent Operation. Fixed 15 min overrun timer. Variable speed options selectable at install.

**Model** VASF100TV **Stock Ref** 479086

#### VASF100HTV (Variable Speed, Intermittent, Humidity Timer)

Intermittent Operation. Humidity controlled with fixed 15 min timer overrun. Variable speed options selectable at install.

**Model** VASF100HTV **Stock Ref** 479087

#### VASF100TC (Variable Speed, Continuous, Timer)

Fixed 15 min overrun timer. Continuous running fan with variable speed selectable at install.

**Model** VASF100TC **Stock Ref** 479088

#### VASF100HTC (Variable Speed, Continuous, Humidity Timer)


Humidity controlled with fixed 15 min timer overrun. Continuous running fan with variable speed selectable at install.

**Model** VASF100HTC **Stock Ref** 479089

Accessories

Model	Stock Ref
Window Kit	442947
Wall Kit White	254102
Wall Kit Brown	254100
Internal Fit Wall Kit White + Backdraught Shutter	474779
Internal Fit Wall Kit Brown + Backdraught Shutter	474780


Dimensions (mm)



A	B	C	D	EØ
160	117	37	80	99

Weight 0.7kg

Performance Guide



	Model	Speed	l/s	Watts	Warranty (years)
2 Speed	VASF100B/T/HT	Low	6	2.7	2
		High	15	4.8	
Variable Speed	VASF100BV/TV/HTV	Min	6	1.7	5
		Max	22	7.5	
	VASF100TC/HTC	Adjustable Trickle	6 - 15	1.7 - 5	5
		Boost	Adjustable Trickle + 10 (Up to a max of 22 installed)	7.5	

All performance testing was done in "through the wall conditions" - installed with 400mm rigid ducting and an exit terminal.