

VES 150mm Range


- Suited for kitchen, utility or large bathroom Ventilation
- Quiet and efficient
- Extract rate of 230m³/hr, 64 litres per second
- ABS thermoplastics for strength, durability, aesthetics and easy cleaning
- Single phase induction motor with pre-oiled bearings for a long, maintenance free life
- Pullcord, timer and humidistat version available
- Designed to comply with the Building Regulations on Ventilation (F1)



Slimline Bathroom Fan

The VES range offers performance of 64l/s whilst being slimline and blends in when surfaced mounted to offer an unobtrusive finish. High performance makes the 150mm perfect for kitchen use.

Electrical

220-240V AC 50Hz . Single Phase consuming 14 Watts. The fan is double insulated and does not require an earth. All wiring must comply with current IEE regulations. A double pole isolating switch, have a contact separation of at least 3mm in all poles must be used with a 3amp fuse fitted.

Additional Data

Maximum pressure: 50 Pa
Fan Speed: 2400 rpm
Sound: 41dB(A)
Maximum operating temperature: 40°C

Models

VES150S
Standard model for remote switching

VES150P
As above supplied with Pullcord switch.

VES150T
Timer model incorporating integral adjustable electronic timer (1-20mins).

VES150H
Humidity control which is adjustable between 40% RH and 95% RH.

VES150HP
As above with pullcord override switch. Requires no switched live.

Dimensions (mm)

